



## SBTL5000 Series

**SBTL5000** Single Lane Swing Barrier Turnstile

**SBTL5011** Single Lane Swing Barrier Turnstile

(w/ controller and RFID reader)

**SBTL5022** Single Lane Swing Barrier Turnstile

(w/ controller and fingerprint & RFID reader)

The ZKTeco SBTL5000 single lane swing barrier turnstile is an elegant high-performance entrance control system designed for high-traffic volume.

The SBTL5000 is a single lane swing barrier turnstile series designed for smooth and silent operation and draws very little power. It is made of stainless steel which makes SBTL5000 highly durable.

SBTL5000 barriers are normally held in a locked position, thus denying access to the secured side. Upon SBTL5000's reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers swing automatically, thus allowing users passage to the secured side.

SBTL5000 provides both security and convenient space, all in a very durable and elegant compact design.

### Features

#### Reliability

- SUS304 stainless steel case ensures long-lasting durability
- High quality electrical components Safety Features.
- All smooth finishing. No exposed screws.
- Ergonomic design makes card and fingerprint authentication fast & simple for users.

#### Built-in Reader Integration

- SBTL5000 series already integrated with customers' preference for either card or fingerprint access control reader which greatly reduces installation time & expenses.
- SBTL5000 series and associated access control readers have passed the factory test before shipment.
- ZKTeco provides the plug&play device with the lowest price in the whole industry.

#### Simplification

- Simplify structure and connection, easy to maintain.
- Control board with LCD screen, easy to operate.

# Specifications

Power requirements	AC 100 ~ 120V/200 ~ 240V, 50/60Hz	
Working temperature	-28°C~60°C	
Working humidity	20%-95% (Non-condensing)	
Working environment	Indoor	
Speed of throughput	RFID	Maximum 30/ minute
	Fingerprint	Maximum 25/ minute
Lane width(mm)	650	
Footprint(mm*mm)	1400*1010	
Dimensions(mm)	L=1400, W=180, H=1000	
Dimension with packing(mm)	L=1500, W=260, H=1100	
Net weight(kg)	120	
Weight with packing(kg)	150	
Cabinet material	SUS304 Stainless Steel	
Lid material	Tempered Glass	
Barrier material	Tempered Glass	
Barrier movement	Swing	
Emergency mode	Y	
Security level	Medium	
MCBF	2 million	

# Dimensions (mm)

